



شركة الطبيعة لانتاج الاصباغ المحدودة

Al-Tabieaa Paints Producing Co.

Technical Data Sheet

Al-Marjan Anti-Fungus Emulsion

DESCRIPTION	Al-Marjan Anti-Fungus Emulsion is high quality emulsion paint based on very special acrylic resin designed to resist rot, fungus and bacteria with very good adhesion , excellent washability. It is available in an endless color choice.
RECOMMENDED USE	Al-Marjan Anti-Fungus Emulsion can be used on all Interior and Exterior concrete, gypsum and wooden walls for hospitals, schools, food factories, food stores and food preparations units.
TECHNICAL INFORMATION	
Colors	As per Al-Tabieaa shade card.
Finish	Smooth surface finish
Specific Gravity	1.57 ± 0.02
Solid by Weight %	60 ± 2%
Covering Rate	15 m ² /Lit. at 40 micron film
Drying Time at 30 °C	Touch dry : 15-20 min. Recoatible: 1-2 hrs. Full cure 24 hrs
SURFACE PREPARATION	
All surfaces to be painted must be clean, dry and sound free of faults, oils, grease, dust and contaminants and should be prepared as per national and international standards for surface preparations like SSPC 13-NACE 6	
APPLICATION DATA	
Application Methods	Brush, Roller or Spray.
Thinning / Cleaning of Tools	Water
Mixing Ratio	10-20%
CONDITIONS DURING APPLICATION	
The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.	
MISCELLANEOUS DATA	
STORAGE	Al-Marjan Anti-Fungus Emulsion should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	24 months.



شركة الطبيعة لانتاج الاصباغ المحدودة

Al-Tabieaa Paints Producing Co.

SAFETY / HEALTH

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner.
- Keep out of reach of children.